

Orosz  
10/812,193

In the Specification

Page 20, change the first paragraph to read as follows:

--Turning to Figure 3, shown therein is an illustrative view of the present invention 10 in use. Shown is the present invention 10 comprising a platform or bridge 12 for supporting the weight of a user 22 spaced away from a newly tiled floor 16, the platform having apertures 14 for selectively positioning posts 18 whereby the platform posts are selectively positioned in gaps 20 between various tile sizes, such as 6" X 6", 8" X 8", 12" X 12", 13" X 13", 16" X 16", etc, preventing engagement therewith.

Page 20, change the second paragraph to read as follows:

--Turning to Figure 4, shown therein is a perspective view of the present invention 10. Shown is a perspective view of the present invention 10 comprising a platform, or bridge 12 for supporting the weight of a user spaced away from a newly tiled floor, the platform having multiple apertures 14 that may be threaded at 22 for selectively positioning posts 18 that also may be threaded 22 whereby the platform posts are selectively positioned between tiles preventing engagement therewith.--

Page 21, change the thrid paragraph to read as follows:

--Turning to Figure 8, shown therein is a sectional view of the present invention 10. Shown is a sectional view of the present invention 10 comprising a platform, or bridge 12 for supporting the weight of a user spaced away from a newly tiled floor 16, the platform having apertures for selectively positioning posts 18 whereby the platform posts are selectively positioned between tiles preventing engagement therewith. Also shown are the floor 30 20 and gaps 20.--